SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006 (REACH)

1. Substance/preparation and company name.

Trade Name Luzar Aerotermia Conc.

Typical Applications Additive for aerothermal circuits.

Company Sucesores de Carmelo Pérez Martínez

Ctra. Castellón Km 3,700 Polígono la Unión, nave 3 E-50.013 Zaragoza (Spain) Phone: +34 976 42 18 50

e-mail: carpemar@carpemar.com

Emergency phone no. +34 91 562 04 20

2. Hazard identification.

Classification of the substance or mixture.

Label elements.

Label according to Regulation (CE)N° 1272/2008 [CLP]

The product is not subject to labeling.

Other hazards.

Unknown.

3. Composition/Information on ingredients.

Propylene glycol with corrosion inhibitors.

Chemical name CAS-No EC number % Pict. Phrases 1,2-Propanediol 57-55-6 200-338-0 >85%

Revision date: Sept-20 1 of 10

4. First aid measures.

General advice Remove contaminated clothing.

On contact with eyes Wash affected eyes for at least 15 minutes under running

water with eyelids held open.

On skin contact Wash thoroughly with soap and water.

If inhaled If difficulties occur after mist/aerosol has been inhaled

remove to fresh air and seek medical attention.

On ingestion Rinse mouth and then drink water (two glasses at the

most). Consult doctor if feeling unwell.

Note to physician Symptomatic treatment (decontamination, vital functions),

no known specific antidote.

5. Fire fighting measures.

Suitable extinguishing media: Water spray, alcohol resistant foam, dry

extinguishers, carbon dioxide (CO₂)

Specific hazards Evolution of fumes/fog. Vapours heavier than air.

Special protective equipment In case of fire, wear a self contained breathing

apparatus.

Further information Contaminated extinguishing water must be disposed

according to official regulations.

6. Accidental release measures.

Personal precautionsUse personal protective clothing.

Do not inhale vapours/aerosol.

Environmental precautions Do not discharge into drains, surface waters,

ground water.

Methods for cleaning up/taking up

Large amount: Pump off products.

<u>Residues/spills:</u> Bind the liquid by using a suitable absorbent material and dispose it

according to the regulations

Revision date: Sept-20 2 of 10

7. Handling and storage.

Handling Ensure thorough ventilation of stores and working

areas.

Protection against fire and

explosion

Take precautionary measures against static discharges.

If exposed to fire, keep containers cool by spraying

with water.

Storage Containers should be stored tightly sealed in dry

place. Since zinc is not compatible with ethylene glycol, storage in galvanized containers is not

recommended.

8. Exposure controls and personal protection

General safety and hygiene measures: Wash hands and forearms after handling.

Do not smoke, eat or drink during

manipulations.

Personal protective equipment:

Respiratory protection: Only in case of release of fumes/fog. Well ventilated areas

are recommended for manipulation.

Required when vapors/aerosols are generated. Filter A-

(P2)

Hands: Chemical resistant protective gloves are recommended.

Eyes: Safety glasses with side-shields.

DNEL (Workers):

Substance		Ac	ute	Long Term	
		Systemic	Local	Systemic	Local
1,2 Propanediol	Ingestion	Not relevant	Not relevant	Not relevant	Not relevant
CAS 57-55-6	Skin Contact	Not relevant	Not relevant	Not relevant	Not relevant
CE: 200-338-0	Inhalation	Not relevant	Not relevant	186 mg/m ³	10 mg/m^3

DNEL (Consumers):

Carbata	Cribatanaa		ute	Long Term		
Substance		Systemic	Local	Systemic	Local	
1,2 Propanediol	Ingestion	Not relevant	Not relevant	Not relevant	Not relevant	
CAS 57-55-6	Skin Contact	Not relevant	Not relevant	Not relevant	Not relevant	
CE: 200-338-0	Inhalation	Not relevant	Not relevant	50 mg/m^3	10 mg/m^3	

Revision date: Sept-20 3 of 10

PNEC Values

Substance	Fresh Water	Sea Water	Water (Intermittent Releases)	Fresh Water Sediment	Sea Sediment	Soil	Sewage Treatment Plant
1,2 Propanediol	260 mg/l	26 mg/l	183 mg/l	572 mg/Kg dry	57,2 mg/Kg dry	50 mg/Kg dry	20.000 mg/l

9. Physical and Chemical properties.

Physical state Liquid Color Blue

Odor Weak, characteristic

pH 8-9.5 Boiling point/range >140°C Solidification temperature <-45°C

Vapor pressure at 20°C 0.1 mbar at 20°C

Flash point >100°C
Lower explosion limit 2,6% V/V
Upper explosion limit 12,6% V/V
Ignition temperature >200°C

Density 1.03-1.06 g/cc at 20°C

Solubility in waterUnlimited

Solubility in other solvents Soluble in polar solvents.

10. Stability and reactivity.

Hazardous reactionsNo hazardous reactions if stored and handle

as prescribed.

Substances to avoid Powerful oxidizing agents and strong acids.

Galvanized and zinc containers.

Hazardous decomposition productsNo hazardous decomposition products if

stored and handle as prescribed.

Revision date: Sept-20 4 of 10

11. Toxicological data.

1,2 Propanediol data:

Acute Toxicity:

Exposure	Parameter	Test	Value	Exposure time	Specie	Value
Ingestion	DL50	OCDE 401	22.000 mg/Kg	-	Rat	Experimental
Skin Contact	DL50	OCDE 402	>2000 mg/Kg.	24 h	Rabbit	Experimental
Inhalation	CL50	OCDE 403	317042 mg/l	2 h	Rabbit	Experimental

Conclusion:

Acute Oral toxicity: Low Acute Dermal toxicity: Low Acute Inhalation toxicity: Low

Corrosion o irritation:

Exposure	Result	Test	Exposure time	Specie	Value
Ingestion	No irritating	OCDE 405	24, 48, 72 h	Rabbit	Experimental
Skin Contact	No irritating	OCDE 404	24, 48, 72 h	Rabbit	Experimental
Skin Contact	Slightly irritating	Patch	24 h	Human	Experimental

Conclusion:

Not classified as irritating to the skin. Not classified as irritating to eyes.

Respiratory or Skin sensitization:

Exposure	Result	Test	Exposure time	Specie	Value
Skin Contact	not sensitizing	OCDE 429		Rat	Experimental
Skin Contact	not sensitizing	Patch	24 h	Human	Experimental
Inhalation	No relevant				

Conclusion:

No skin sensitizer.

Not available data for respiratory sensitization.

Revision date: Sept-20 5 of 10

Specific Target Organ Toxicity.

Exposure	Test	Value	Effect	Exposure time	Specie	Value
Ingestion	OCDE 429	1700 mg/Kg day	No effect	>102 weeks(daily, 5 days/week)	Rat	Experimental
Skin Contact	Patch	0,02 ml (twice a week)	No effect	10 weeks (daily, 5 days/week)	Mouse	Experimental
Inhalation	LOAEC	160 mg/m ³	No effect	90 days	Rat	Experimental

Conclusion:

Subchronic dermal toxicity: Low. Subchronic oral toxicity: Low Subchronic inhalation toxicity: Low

Germ cell mutagenicity (in vitro)

Result	Test	Test substrate	Effect	Value
Negative	Others	Bacteria (S.typhimurium)		Experimental
Negative	OCDE 473	Human lymphocytes		Experimental

Carcinogenicity

Exposure	Test	Value	Exposure time	Specie	Valor	Effect
Inhalation	NOAEC	>350 mg/m ³ air	18 months	Rat	Experimental	No effect
Skin Contact	NOAEL	0,02 ml (twice per week)		Mouse	Experimental	No effect
Ingestion	NOAEL	1700 mg/Kg.	2 years	Rat	Experimental	No effect
Ingestion	NOAEL	3040 mg/Kg.	105 weeks	Rat	Experimental	No effect
Ingestion	NOAEL	2390 mg/Kg.day	105 weeks	Mouse	Experimental	No effect

Reproductive toxicity

Study	Test	Valor	Exposure time	Specie	Effect
Effect on fertility	OCDE 416	10100 mg/Kg day		Mouse	No Effect
Developmental Toxicity	OCDE 414	10400 mg/Kg day	9 days	Mouse	No Effect

Conclusion CMR

Not classified for carcinogenicity.

Not classified for mutagenic or genotoxic toxicity.

Not classified for reproductive toxicity or developmental toxicity.

Revision date: Sept-20 6 of 10

12. Ecological data.

Data for 1,2 Propanediol

Toxicity

Study	Parameter	Test	Value	Test Time	Specie	Environment
Acute Toxicity fishes	CL50		40613 mg/l	96 h	Oncorhynchus Mykiss	Fresh Water
Acute Toxicity invertebrates	CL50	EPA 600/4- 90/027	18340 mg/l	48 h	Ceriodaphnia Dubia	Fresh Water
Acute Toxicity invertebrates	CL50	FIFRA 72-3	18800 mg/l	96 h	Americamysis bahía	Sea Water
Threshold limit algae	CE50	OCDE 201	19000 mg/l	96 h	Pseudokircheneriell a subcapita	Fresh Water
Threshold limit algae	CE50	OCDE 201	19100 mg/l	96 h	Skeletonema Costatum	Sea Water
Acute Toxicity fishes	ChV	ECOSA R	2500 mg/l	30 days		Fresh Water
Acute Toxicity aquatic invertebrates	NOEC	EPA 600/4- 89/001	13020 mg/l	7 days	Ceriodaphnia Sp.	Fresh Water
Toxicity aquatic microorganisms	NOEC		20000 mg/l	18 days	Pseudonomas Putida	Fresh Water
Toxicity sedimentary organisms	CL50		69836 mg/Kg sediment	10 days	Corophium volutator	Fresh Water

Conclusion

Harmless to fish (CL50 (96h) > 1000 mg/l) Not harmful to invertebrates (CE50 (48) >1000 mg/l) Harmless to algae (CE50 (72h) >1000 mg/l) Harmless to bacteria (CE50 >1000 mg/l)

Persistence and degradability

Biodegradation in water:

Test	Value	Test Duration	Value
OCDE 301F	81,7%	28 days	Experimental

Biodegradation in soil:

Test	Value	Duration	Value	
Others	98%	105 days	Experimental	

Phototransformation aire (DT50 water)

Revision date: Sept-20 7 of 10

Test	Value	Conc. Radicals OH	Value
AOPWIN v1.92	0,83 days	$1.5 \text{x} 10^6 / \text{cm}^3$	QSAR

Phototransformation water (DT50 water)

Test	Value	Conc. Radicals OH	Value
Others	2,3 years	$1.5 \times 10^6 / \text{cm}^3$	Calculate

Conclusion:

Readily biodegradable in water

Biodegradable in soil under anaerobic conditions.

Photodegradation in water occurs slowly.

Bioaccumulation potential

Log Pow

Test	Value	Temperature	Value
OCDE 107	-1,07	20,5°C	Experimental

Percentage distribution

Test	Air Fraction	Biota Fraction	Sediment Fraction	Soil Fraction	Water Fraction	Value
Level of Mackay III	2,98%		0,07%	48,1%	48,8%	Calculate

Additional information Do not release into natural waters.

13. Disposal considerations

Contaminated packaging

Uncontaminated canisters can be re-used. Canisters that cannot be cleaned should be disposed of in the same manner as the contents.

Packaging that cannot be cleaned should be disposed according to the applicable law in the same way that content.

Revision date: Sept-20 8 of 10

Waste code: (91/689 / EEC Commission Decision 2001/118 / EC, O.D. L47 of 16/2/2001): 07 01 0* (other organic solvents, washing liquids and mother liquors); 16 01 14* (antifreeze containing dangerous substances)

LWCA (Netherlands): KGA category 03 Hazardous waste (91/689 / EEC)

Disposal methods:

Recycling by distillation

Delete incinerator for solvents prior authorization of pollution control agency to discharge water treatment station

No discharge into surface water

Packaging / Container:

Waste material code packaging (91/689 / EEC Commission Decision 2001/118 / EC, O.D. L47 of 16/2/2001): 15 01 10 * (packaging containing residues of hazardous substances or contaminated by them)

Disposal of contaminated packaging: Completely empty containers

Disposal in an authorized waste collection point

Recommended cleaning method: cleaned by recycling center or specialized company

14. Transport information

Not classified as hazardous under transport regulations. (ADR / RID / ADNR / IMDG/GGVSee ICIAO/IATA)

15. Regulatory information

Regulations of the European Union (labeling) / National legislation / Regulations:

Hazard symbol

H-phrases:

P-phrases:

16. Further information.

H statements:

Health hazards:

H301: Toxic if swallowed.

H319: Causes serious eye irritation.

Revision date: Sept-20 9 of 10

H332: Harmful if inhaled.

H412: Harmful to aquatic life with long-lasting effects.

Abbreviations and acronyms:

PNEC: Predicted No Effect Concentration.

Intermittent Release: Intermittent but only recurring infrequently i.e. less than once per month and for no more than 24 hours.

This safety data sheet is intended to provide information and recommendations as to: 1. how to handle chemical substances and preparations in accordance with the essential requirements of safety precautions and physical, toxicological and ecological data. 2. How to handle, store, use and transport them safety.

No liability for damage occurred in connection with the use of this information or with the use, application, adaptation or processing the products here described will be accepted. No liability will be accepted for damage indirectly incurred.

We provide this information data according to our present level of knowledge and experience. No assurances concerning the characteristics of our product are hereby furnished.

Revision date: Sept-20 10 of 10